



Number	A	B	C	D	E	F
20	10.350	9.150	5.715	8.150	8.100	11.750
30	13.525	12.325	8.890	11.325	11.275	14.925
40	16.700	15.500	12.065	14.500	14.450	18.100
50	19.875	18.675	15.240	17.675	17.625	21.275
60	23.050	21.850	18.415	20.850	20.800	24.450
70	26.225	25.025	21.590	24.025	23.975	27.625
80	29.400	28.200	24.765	27.200	27.150	30.800
90	32.575	31.375	27.940	30.375	30.325	33.975
100	35.750	34.550	31.115	33.550	33.500	37.150

- NOTES:
- Housing material: LCP (UL94V-0).
 - Terminal material: phosphor bronze. The overall 60u"~200u" Nickel Plated(lead-free). Welding pin gold plated 2u"~8u" MIN. contact point gold plated 4u" MIN. (Pb free).
 - Fitting nail material: Brass. The overall 80~120u" Nickel Plated (lead-free). Plated with matte Tin(100%) 80u" MIN. (lead-free).
 - "▲" Important dimensions.
 - PART NO. Specifications: 123020-20XX50-HF

Number of positions

PCB LAYOUT

				UNLESS OTHERWISE SPECIFIED TOLERANCES ARE		客户图 Drawings		北极大电子科技有限公司 BEIJIDA ELECTRONICS TECHNOLOGY CO. LIMITED						
				X. ±0.20		APPROVED Tianshu Chen 2019-04-15		DATE 2019-04-15		COMPUTER NO 123020-20XX50-HF				
				X.XX ±0.10		CHECKED Tianshu Chen 2019-04-15		DATE 2019-04-15		NAME BTB0.635-3代浮动式母座 (定位柱)				
				X.XXX ANG. ±0°30'		DRAWN Loren Lu		DATE 2019-04-15		SIZE A4	SCALE 4:1	REV B		
▲ Revision of plating specification		Lu	2020-05-20	UNIT MM	SER	REVISIONS	CHK	DATE	4	5	6	7	8	9